

ISLAND EPOXSEAL MARINE EPOXY

DESCRIPTION :

Island Epoxseal Marine Epoxy is a two component epoxy-polyamide based filler and adhesive developed as an excellent patching compound for epoxy and other selected paint systems. It exhibits good bonding strength and tough cured film.

USE :

As adhesive for wood and other substrates. It is also used as putty for epoxy and other suitable system.

COLOR :

Gray and Red

APPLICATION :

Putty Knife

MIXING RATIO :

1 part of Base (Part A) : 1 part of Hardener (Part B)

PHYSICAL PROPERTIES :

Volume Solid : 100%

DRYING TIME :

Dry to touch : 30 minutes

Dry to handle : 7 hours

Dry hard : 24 hours

THEORETICAL COVERAGE :

2.5-4.0 sq.m. / Liter set @ approximately 1mm thickness

PACKAGING :

1L and 4L Part A (Base) ;

1 L and 4L Part B (Hardener)

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.